



### Name

Frost Floor drain assembly medium duty cast iron grating circular, medium sump body cast iron vertical outlet 4" BSP

### Code

31.0094

### Description

Frost floor drain with 200mm circular flat grating, medium sump body and threaded outlet.  
Supplied with membrane clamp.  
Connect to pipework using an adaptor.  
Untrapped medium duty assemblies for use in floors with an asphalt or composition surface membrane and subject to light vehicular traffic.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997  
80%-97% recycled materials  
100% recyclable

Ductile iron BS EN 1563 & 1564  
Greater than 80% recycled materials  
100% recyclable

### Body Material

CAST IRON

### Body Type

UNTRAPPED

### Grating Material

DUCTILE IRON

### Flow Rate

N/A

### Outlet Type

THREADED

### Load Rating

L15 To BS EN 1253

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.