



Name

Frost Floor drain assembly heavy duty with clamp, 320mm grating square, large sump body cast iron vertical outlet 150mm DIA

Code

31.0219

Description

Frost floor drain with 320mm square grating, large sump body and spigot outlet.

Supplied with membrane clamp.

Connect directly to pipework.

Untrapped assemblies are for use in unfinished, screeded or paved concrete floors such as parking areas, warehouses and plant rooms.

Please note that the overall height of assemblies will vary according to membrane thickness.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997

80%-97% recycled materials

100% recyclable

Ductile iron BS EN 1563 & 1564

Greater than 80% recycled materials

100% recyclable

Body Material

CAST IRON

Body Type

UNTRAPPED

Grating Material

DUCTILE IRON

Flow Rate

N/A

Outlet Type

SPIGOT

Load Rating

M125 To BS EN 1253

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.