



## Name

Frost Cold Roof drain assembly - cast iron grating, fixed 240mm circular, large sump body with clamp, vertical threaded outlet 4" BSP

## Code

33.0054

## Description

Frost Cold Roof drain assembly with fixed 240mm circular flat grating, large sump body and vertical threaded outlet 4" BSP  
Supplied with body and clamp.  
Suited to cold roof construction where the waterproof membrane is located on top of the roof deck.

Cast Iron Grade EN-GJL-150 to BS EN 1561:1997  
80%-97% recycled materials  
100% recyclable

Ductile Iron BS EN 1563 & 1564.  
Greater than 80% recycled material  
100% recyclable  
Cast with the ductility of steel and more than doubling the tensile strength of cast iron.

## Body Material

CAST IRON

## Body Type

N/A

## Grating Material

DUCTILE IRON

## Flow Rate

10.70 l/s

## Outlet Type

THREADED

## Grating Type

FLAT

## Load Rating

N/A

## Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.