




Name

Frost Floor drain 150mm square stainless steel grating 3mm slots with medium sump body and threaded outlet size 4" BSP

Code

31.0485

Description

Frost floor drain assembly with height adjustable Slimline Heel Proof 150mm square stainless steel slotted grating, medium sump body and threaded outlet.

Membrane clamp & collar are an optional extra (31.2030). Can be trapped using a removable trap (31.9510).

Quick and easy to install

Maintenance free and durable

Connect body to all types of pipework in general use, using adaptors.

Stainless steel for use in areas where they contribute to the aesthetic appeal of an area.

Stainless Steel BS EN 10088-1:2005
Grade 1.4301 (304) or (316) if specified
Average recyclable content 75%-85%

Cast iron Grade EN-GJL-150 to BS EN 1561:1997
80-97% recycled materials

100% recyclable

Body Material

CAST IRON

Body Type

UNTRAPPED

Grating Material

STAINLESS STEEL

Flow Rate

N/A

Outlet Type

THREADED

Load Rating

L15 To BS EN 1253-1:2015

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.