
frost DRAINAGE

Product Specification





Name
Frost Floor drain 150mm square stainless steel grating 3mm slots with large trapped sump body and threaded outlet size 4" BSP

Code
31.0985

Description
Frost floor drain assembly with height adjustable Slimline Heel Proof 150mm square stainless steel slotted grating, large trapped sump body and threaded outlet.
Membrane clamp & collar are an optional extra (31.2030).
Quick and easy to install
Maintenance free and durable
Connect body to all types of pipework in general use, using adaptors.
Stainless steel for use in areas where they contribute to the aesthetic appeal of an area.

Stainless Steel BS EN 10088-1:2005
Grade 1.4301 (304) or (316) if specified
Average recyclable content 75%-85%

Cast iron Grade EN-GJL-150 to BS EN 1561:1997
80-97% recycled materials
100% recyclable

Body Material
CAST IRON

Body Type
TRAPPED To BS EN 1253-1:2015

Grating Material
STAINLESS STEEL

Flow Rate
N/A

Outlet Type
THREADED

Load Rating
L15 To BS EN 1253-1:2015

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.