



### Name

Frost Aluminium Inverted Roof drain assembly - fixed dome 220mm and 150mm gravel guard, medium sump body with clamp, vertical threaded outlet 4" BSP

### Code

34.0304

### Description

Frost Inverted Roof drain assembly, fixed dome 220mm and 150mm gravel guard, medium sump body with clamp, vertical threaded outlet 4" BSP. Supplied with grating and clamp. Rainwater outlets with domed gratings are suited to inverted roof construction where the waterproof membrane is located above the roof deck but below the insulation layer. The stainless steel gravel guard prevents ballast entering the drainage system during maintenance. Gravel guards higher than 150mm are available.

Aluminium LM 6 to BS EN 1599-4:1999

### Body Material

ALUMINIUM

### Body Type

N/A

### Grating Material

ALUMINIUM

### Flow Rate

2.29

### Outlet Type

THREADED

### Grating Type

DOMED

### Load Rating

N/A

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.